

40mm Stroke Mini Crimping Applicator

RSA-EA-20E





Feature

- Adopt disk type adjustment structure, two connection points with crimping machine guarantee the stability and high adjustment accuracy.
- ▶ The adjustment accuracy of C.H./i.h. is 0.02mm. The adjustment scope is 2mm. Clear hand feeling and scale fully fill demands of high processing standard.
- Simple and direct feeding structures make sure the high feeding accuracy ,guarantee the right position of the each terminal. Obvious scale of feeding pitch make sure the pitch adjustment easy and convenient.
- ▶ Professional and universal design, excellently fit Komax , AMP, and Mecal 's Semi/Auto terminal crimping machine
- Standard equip 7 digits stroke counter, record the crimping times clearly, easy to handle the PM time.
- New terminal guiding structure and front locking structure which can lock the guiding component in front side after the R angle of forward and backward settled. No need to remove the applicator from crimping machine, which will increase the efficiency a lot.
- Cross analyze report and CMK report can be provide for each applicator.
- ▶ QPQ surface treatment technology , highly increase the capacity of rust-proof and wear proof .
- ▶ Unique ID for each part, which increase the convenience of further maintenance.

Specification

М	lodel	RSA-EA-20E
De	escription	Side Feed/Mechanical
Cr	rimping Height	135.78mm
St	troke	40mm
Fe	eeding Pitch	27mm (max)
Te	erminal Thickness	1.2mm(max)
Cr	ross section of Cable	0.08mm2 - 10mm2
W	/eight	4.2KG
Di	imension	L140mm x 112mm H158mm