

Wire Harnesses Braiding Machine(Servo+PLC Touch Screen)

(24/32/48 spindles) **RSA-WBM-11024/11032/11048**



Feature

- ▶ Mainly used for wire harness braiding. Automobile assembly harnesses, special vehicle harnesses, aircraft harnesses, aerospace harnesses, etc.
- ▶ Improved flexibility. Braiding density is adjustable, which can work for different requirements and purpose.
- ▶ User-friendly. The buttons on the control panel are simple and clear, which make sure quick and easy operation.
- ▶ Take-up wheels can be rotated forward or backward to achieve normal and reverse braiding and hide the braiding joint, thus improving the overall beauty of the wire harness.
- ▶ Safety covers are applied to ensure safety while making manual operation more convenient.

Specification

Model	RSA-WBM-11024	RSA-WBM-11032	RSA-WBM-11048
Head Number	1	1	1
Spindle Number	24	32	48
Bobbin Number	48	64	96
Braiding Method	Ø57*210mm	Ø57*210mm	Ø57*210mm
Dial O.D.	110mm	110mm	110mm
Dial rpm	≤260rpm	≤280rpm	≤280rpm
Control Way	Servo+PLC Touch Screen	Servo+PLC Touch Screen	Servo+PLC Touch Screen
Power	1.1KW (Servo+PLC Touch Screen)	1.1KW (Servo+PLC Touch Screen)	1.5-2KW (Servo+PLC Touch Screen)
Voltage	220V/380V (customizable)	220V/380V (customizable)	220V/380V (customizable)
Weight	400kg	450kg	500kg
Dimension	L1100*W1000*H1900mm	L1100*W1000*H1900mm	L1200*W1200*H1900mm