

Fully Automatically Terminal Crimping Machine

RSE/M-FC-551J



Feature

- ▶ Step motor and servo motor drive two configurations for optional to satisfy different demands.
- ▶ Adopt Straight feeding way , can effectually avoid wire of any size stopped up.
- ▶ Twisting device has automatic reset function, so no need to adjust wire size (Optional function)
- ▶ Equipped with signal indicator,easy to eliminate malfunction.
- ▶ CFM, Automatic wire feeder and wire collecting machine (conveyor) can be equipped for extra demand.
- ▶ Safety cover also can be equipped for extra demand.

Specification

Model	RSE/M-FC-551J
Stroke	30mm/40mm
Function	Cutting;Stripping; Crimping; Twisting(Optional)
Cutting Length	40mm-99999.9mm
Stripping Length	Front end 0.1mm-15mm Rear end 0.1mm-8mm(custom make 20mm)
Twisting Length	2mm-12mm(custom make 20mm) (Optional function)
Guiding Tube Diameter	1.5mm-5mm
Wire Size	AWG32-AWG#14 (0.035mm ² -2.5mm ²) or Customized
Crimping Pressure	2.0T
Productivity	4200-4600pcs/hour L=100 Pcs
Crimp Location	Adjusted Digitally
Air Pressure	5-7kgf
Tool Material	Tungsten steel / High-speed steel
Power	AC 220V/50/60HZ
Weight	About 200kg
Dimension	700(L) *600 (W) *1400(H)MM