

Heat Shrink Tubing Machine (Suspended Bracket)

RSM-HSM-1040



Feature

- ▶ The suspended design ensures even heat distribution and prevents product deformation.
- ▶ Higher productivity with larger working area of high-temperature resistant PTFE mesh belt and continuous feeding mode.
- ▶ Widely applicable. Different sizes of harnesses can be baked thanks to compact suspended design and movable shrinking area.
- ▶ Work temperature and conveyor speed are adjustable to tailor to different products' shrinking.
- ▶ Safe and durable. Avoid high temperature around the machine by independent control box and double-layer heating box with insulation cotton (temperature resistance: 1200°C).
- ▶ Bracket is customizable according to your production line and production requirement.

Specification

Model	RSM-HSM-1040
Heating Temperature	0-260°C
Heating Method	Dual temperature control (double-sided heating)
Heating Tube	Far Infrared Heating Tube
Conveyor Speed	0-6 meters/min
Conveyor Load	20kg
Conveyor Material	High-temperature PTFE mesh belt
Configuration	Hot air blower, cooling device, conveyor belt guide
Power	4KW
Voltage	AC220V/50HZ (single phase) (110V available)
Weight	100KG
Heating Chamber	L1000mm×W400mm×H280mm
Heating Zone	L1000mm×W360mm×H100mm
Bracket Dimension	L1600mm×W700mm×H1200mm