

Pneumatic Hot Stamp Marking Machine

RSM-HSM-11Q



Feature

- ▶ Uniform and crisp impressions guaranteed by cylinder instead of hand-operated stamping.
- ▶ Suitable for surface hot stamp of PVC flexible tubing, HST, flexible film, insulated wire, nylon, and PTFE.
- ▶ Hot stamping ribbon comes in black and white, mounted on the phenolic wheel. Each roll yields 8,000 impressions, printing 1–11 characters per cycle.
- ▶ Hot stamp depth, stamp speed, and temperature are all adjustable.

Specification

Model	RSM-HSM-11Q
Application	Hot stamp on PVC flexible tubing, HST, flexible film, insulated wire, nylon, and PTFE
Wire O.D.	Φ3mm-Φ6mm
Number of Character Wheel	11pcs
Character Wheel Width	2.5mm
Character Wheel Material	Copper, 45# steel
Character Size	2.4×2.4; 1.8×1.8; 1.2×1.2 (Customized acc. to wire size)
Character Face	Flat/Curved
Number of Characters per Cycle	1—11 digits
Hot Stamping Ribbon	Black, White
Stamp Count/Impressions	8000pcs per roll
Work Temperature	60-180°C (depends on the wire insulation material)
Voltage	AC220V
Power	80W
Weight	About 35kg
Dimension	L355mm×W280mm×H360mm