

Heat Shrink Tubing Machine (Suspended Bracket)

RSM-HSM-848



Feature

- ▶ Suitable for heat shrink tubing of small-sized products such as wire harness, heat shrink film packaging, PCBs, inductor coils, copper busbars, hardware accessories.
- ▶ The suspended design ensures even heat distribution and prevents product deformation.
- ▶ Track-type design for automatic wire unloading.
- ▶ Work temperature and conveyor speed are adjustable to tailor to different products' shrinking.
- ▶ Safe and durable. Avoid high temperature around the machine by independent control box and double-layer heating box with insulation cotton (temperature resistance: 1200°C).
- ▶ Bracket is customizable according to your production line and production requirement.

Specification

Model	RSM-HSM-848
Heating Temperature	0-260°C
Heating Method	Dual temperature control (double-sided heating)
Heating Tube	Far Infrared Heating Tube
Conveyor Speed	0-6 meters/min
Conveyor Load	20kg
Conveyor Material	High-temperature PTFE mesh belt
Configuration	Hot air blower, cooling device, conveyor belt guide
Power	3.6KW
Voltage	AC220V/50HZ (single phase) (110V available)
Weight	85KG
Heating Chamber	L800mm×W480mm×H280mm
Heating Zone	L800mm×W400mm×H150mm
Bracket Dimension	L1600mm×W480mm×H1200mm