



Intelligent Terminal Crimping Machine (with Servo Motor) RSM-STC-10T/20T/30T/40T/50T



Feature

- ▶ High crimping accuracy guaranteed by 1μm optical encoder.
- ▶ Available for barcode scanner connection, which can dock ERP management system.
- ▶ Improved crimp quality by storing past crimping data for quality management tracking.
- ▶ User-friendly. Memory/recipes can be stored on HMI, which can quickly crimp terminals of different heights.
- ▶ EMS system can be accessed via local area network. (optional computer version)

Specification

Model	RSM-STC-10T	RSM-STC-20T	RSM-STC-30T
Stroke	40mm	50mm	50mm
Cable Range	2.5-35mm ²	2.5-95mm ²	2.5-180mm ²
Crimping Accuracy	±0.03mm	±0.03mm	±0.03mm
Applicable Applicator	Hexgon crimping applicator, square crimping applicator, F-terminal crimping applicator		
Power	1.5KW	2KW 10NM	2KW 15NM
Weight	230kg	About 450kg	About 450kg
Dimension	L540*W350*H785	L560*W400*H985	L560*W400*H985



Model	RSM-STC-40T	RSM-STC-50T
Stroke	50mm	75mm
Cable Range	2.5-200mm ²	2.5-300mm ²
Crimping Accuracy	±0.03mm	±0.03mm
Applicable Applicator	Hexgon crimping applicator, square crimping applicator, F-terminal crimping applicator	
Power	2.3KW 15NM	3KW 18NM
Weight	About 510kg	About 670kg
Dimension	L560*W400*H985	L700*W480*H1225

Workbench (optional)

