


Automatic Tape Wrapping Machine

RSM-TW-850C



Feature

- ▶ Suitable for tape wrapping of thin wire.
- ▶ Integrated auto tape wrapping, tape cutting and wire releasing into one machine. No need to hold the wire harness.
- ▶ Auto tape cutting and tape end pressing to reduce the labor cost.
- ▶ Higher flexibility. Full tape wrapping and multi-section tape wrapping mode are available.
- ▶ Wire twisting is prevented during tape wrapping by synchronous rotation of two pneumatic wire grippers.
- ▶ Higher tape wrapping accuracy guaranteed by PLC and touch screen.

Specification

Model	RSM-TW-850C
Applicable Tape	PVC, flocking, cloth-backed, high-temperature tapes; ideally suited for mica, ceramic, and acetate cloth tapes (with liner).
Wire O.D.	3-10mm
Tape Roll I.D.	Standard Φ38 (other sizes like Φ32, Φ76..., please specify in advance)
Tape Roll O.D.	≤ 110mm
Wrapping Length	Max. 1000mm
Open End Length (Front)	≥15mm
Open End Length (Rear)	≥10mm
Spindle Speed	4500 RPM (Adjustable)
Machine Speed	0-30 (Adjustable)
Cycle Time (at medium speed)	15 sec/m (Full wrap)
Voltage	AC220V/DC24V 50/60HZ (110V available)
Power	1350W
Weight	300KG
Dimension	L1800mm×W700mm×H1070mm
Options	Paper winder; Safety light curtain